

*Estimated N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PER	MITTED. 1	F ANY ITEM	IS No	OT APPLICABLE, THE S	SPACE MUST BE	MARKED TO	INDICATE THAT.	
IDENTITY				PART NO.				
(As shown on Label or package) PDC F-7	17				IF APPLICAL	BLE		
SECTION I								
MANUFACTURER'S					EMERGENC	Y PHONE No.		
NAME Plasti Dip International, Inc.				USA only: 1-800-424-9300 INT'L: 703-527-3887				
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)					REVISIONS # 0002			
3920 Pheasant Ridge Drive								
				MANUFACTURER'S PHONE				
Blaine, MN 55449						ORMATION 1	-763-785-2156	
					DATE MSDS			
						RED May 16 th		
SECTION II - HAZARDOUS INGREDIE	NTS INFOR	MATION. All	l Heal	th Hazards which compris	se 1% or greater o	f the composition	on and all carcinogens	
if 0.1% of the composition or greater.								
HAZARDOUS COMPONENTS CHEMI	CAL and	% Wt.		CAS NO.	OSHA	ACGIH	OTHER LIMITS	
IDENTITY AND COMMON NAMI	E (S)	(OPTIONA	AL)		PEL	TLV	RECOMMEND	
VM&P Naphtha		34.8		64742-89-8	300 ppm	300 ppm	None	
Hexane		14.8		110-54-3	500 ppm	50 ppm	None	
Xylene		12.7		1330-20-7	100 ppm	100 ppm	None	
Acetone		8.1		67-64-1	1000 ppm	500 ppm	None	
Ethylbenzene		3.1		100-41-4	100 ppm	100 ppm	None	
SECTION III - PHYSICAL / CHEMICAL	CHARACT	ERISTICS						
BOILING	SPECIFIC	C GRAVITY (F	$H_20 = 0$	1)	APPROXIMA	TE WEIGHT	PER GALLON (LBS)	
POINT 133 - 286°F	0.82 - 0.84			0.84	6.87			
VAPOR PRESSURE	VAPOR DENSITY EVAPORATION RATE							
186 mmHg @ 20°C	(AIR = 1) Heavier than air (BUTYL ACETATE =			TATE =1) >	1.0			
SOLUBILITY IN WATER		% VOLATILE 65.4			OTHER			
Insoluble	VOC LBS	./GAL 4.5			(IF ANY)	None		
APPEARANCE								
AND ODOR Various Colors, Honey Lik			Odo					
SECTION IV-FIRE AND EXPLOSION H	AZARD DA	TA			_			
FLASH POINT - 10.0°F			FLA	AMMABLE LIMITS	LEL	UE		
(METHOD USED) TCC					0.9		12.8	
EXTINGUISHING								
MEDIA Carbon Dioxide, Dry Che	emical, or Fo	am						
SPECIAL PROCEDURES OF S				0.11.0			i	
FIRE FIGHTING PROCEDURES Self control UNUSUAL FIRE AND	ontained brea	ithing apparatus	s with	a full face piece, operated i	n pressure demand	or other positive	pressure mode.	
EXPLOSION HAZARDS This material is	flammabla	nd may be ignit	tad by	haat sparks flama ar statis	alaatriaity			
HAZARDOUS PRODUCTS FORMED BY		nd may be igini	ieu by	neat, sparks, name or static	electricity.			
FIRE OR THERMAL DECOMPOSITION		Dioxide and/or	Carbo	on Monovide				
EXPLOSIVE LIMITS	Carbon	Dioxide and/or	Caroc	JII WOIIOXIGE				
(% BY VOLUME IN AIR) 0.9 – 12.8								
SECTION V - OPTIONAL HAZARD RAT	TINGS IDEN	TIFICATION	J					
HAZARD RATING	IIIOS IDEI	THICATION	1	National Fire Protection	Association (NFP	A)		
4-EXTREME				National File Flotection	Association (INFT	A)		
3-HIGH				FIRE 3 REACTIVITY	ΓΥ 0 .			
2-MODERATE								
1-SLIGHT								
0-INSIGNIFICANT				HEALTH 2 SPI	ECIAL HAZARDS	None .		
**SEE SECTION IV								
	-				-			



SECTION VI - REACTIVITY AND	D STABILITY DATA					
STABILITY UNSTAI	BLE STABLE X	CONDITIONS T	O AVOID None			
INCOMPATIBILITY (Materials to	Avoid) Strong acids, bases, oxidizing a	gents, selected amin	es with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION	OR BY PRODUCTS Carbon Monoxid	e, Carbon Dioxide				
HAZARDOUS	MAY OCCUR	CONDITIONS T	O AVOID			
POLYMERIZATION	WILL NOT OCCUR X		None			
SECTION VII - HEALTH HAZAR	D DATA					
ROUTES OF ENTRY	INHALATION? Yes SKIN?		TON? Yes EYES? Yes			
HEALTH ACUTE	X See Signs and Symptoms of Exp					
HAZARDS CHRONIC	X Brain and Nervous System Dam	age (Referred to as s	olvents or painters syndrome). Drying or Cracking skin.			
CARCINOGENICITY: IARC 2B						
CLCNG AND						
SIGNS AND	H 1 1 D' ' D ' E'	T 1 TT (1	OL ID The			
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatig					
EXPOSURE	Target Organs: CNS, CVS, PNS, Liver	r, Kidneys, Lungs, R	espiratory System, Skin.			
MEDICAL CONDITIONS CENED	ALLV ACCDAVATED DV EVDOCH	DE Des avistina Has	et Liver Vidney and Lyne discurders			
MEDICAL CONDITIONS GENER	ALLY AGGRAVATED BY EXPOSUR	KE Pie-existing nea	irt, Liver, Kidney and Lung disorders.			
EMERGENCY AND	Ingestion: Contact Physician or Poison	Control Immediatel	V			
FIRST AID	Inhalation: Remove to fresh air. Admi					
PROCEDURES	Eye Contact: Flush with large amounts		·			
	Skin: Wash with soap and water.		p			
SECTION VIII - PRECAUTIONS I	*					
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.					
IN CASE MATERIAL IS	Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam					
RELEASED OR SPILLED	or contain spills. If large spill, notify appropriate state and local agencies.					
WASTE DISPOSAL METHODS D	Dispose of product in accordance with loca	al, county, state and	federal regulations.			
PRECAUTIONS TO BE	Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation.					
TAKEN IN HANDLING						
AND STORAGE						
OTHER	V C	C	14 1 4:4 - 6:			
OTHER PRECAUTIONS	in accordance with Governmental Regu		ld be disposed of in an environmentally safe manner			
SECTION IX - CONTROL MEASU		nations.				
	SPECIFY TYPE) Depending on the Airbo	ma concentration	PROTECTIVE GLOVES			
	SH approved cartridge or supplied air equ		Impervious Gloves			
	AUST Supplemental (if needed)	принене.	SPECIAL None			
	L (GENERAL) To maintain exposure	below PEL's	OTHER None			
EYE PROTECTION	(- ·)		OTHER PROTECTIVE CLOTHING OR EQUIPMENT			
Chemical splash goggles, or approved	emical splash goggles, or approved eye protection. Chemcial Apron/Eye bath/Safety Shower					
WORK HYGIENIC PRACTICES	Wash thoroughly after handling.					
SECTION X - TRANSPORTATION	N INFORMATION (Optional)					
DOT PROPER SHIPPING NAME	Coating Solution	DOT HAZARI	OCLASS 3			
DOT UN NUMBER UN1139	-	DOT PACKIN	G GROUP II			
IATA PROPER SHIPPING NAME	TA PROPER SHIPPING NAME Coating Solution IATA HAZARD CLASS 3					
IATA UN NUMBER UN 1139		IATA PACKIN	NG GROUP II			
SECTION XI - 313 SUPPLIER NO	TIFICATION					
			NG REQUIREMENTS OF SECTION 313 OF THE			
	COMMUNITY RIGHT -TO-KNOW A	CT OF 1986, 40 CF	R 372, (see table on page 1 for CAS # and percent by weight).			
Hexane, Xylene, and Ethylbenzene						
WARNING: THIS PRODUCT CO		THE STATE OF (CALIFORNIA TO CAUSE CANCER AND BIRTH			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	