

*Estimated N/A-Not Applicable N/R-Not Restricted N/E-Not Established

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERM	MITTED.	IF ANY ITEM	IS NOT APPLICABLE,		BE MARKED	TO INDICATE THAT.	
IDENTITY				PART NO.	PART NO.		
(As shown on Label or package) PDC F-		IF APPLICABLE					
SECTION I							
MANUFACTURER'S				EMERGENC	Y PHONE No.		
NAME Plasti Dip Internationa		USA only: 1-800-424-9300 INT'L: 703-527-3887					
		REVISION # 0003					
3920 Pheasant Ridge Drive	ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)						
3720 Theasant Riage Diffe				MANUFACT	TIRER'S PHON	IF.	
Blaine, MN 55449					MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156		
Bianic, Wilv 3344)	DATE MSDS						
				WAS PREPARED May 24, 2007			
SECTION II HAZADDOUG INCDEDIEN	TC INFO	DMATION ALL	II. aldh II. aanda aabiah a				
SECTION II - HAZARDOUS INGREDIEN		KMATION, AII	Health Hazards which co	omprise 1% or grea	ter of the compo	osition and all	
carcinogens if 0.1% of the composition or gu		CI XXII	CLCNO	OCTA	A COTTY	OWNED I IMPE	
HAZARDOUS COMPONENTS CHEMIC		% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS	
IDENTITY AND COMMON NAME	(8)	(OPTIONAL		PEL	TLV	RECOMMEND	
Acetone		29 - 37	67-64-1	1000 ppm	500 ppm	None	
Toluene		20 - 26	108-88-3	200 ppm	50 ppm	None	
Methyl Ethyl Ketone		8 - 13	78-93-3	200 ppm	200 ppm	None	
Xylene		5 - 10	1330-20-7	100 ppm	100 ppm	None	
Ethylbenzene		1 - 3	100-41-4	100 ppm	100 ppm	None	
SECTION III - PHYSICAL / CHEMICAL (CHARAC	TERISTICS					
BOILING	SPECIFIC GRAVITY (H ₂ 0 =1) APPROXIMATE WEIGHT PER GALLON (LBS)						
POINT 133 - 279°F					7.45 – 7.58		
VAPOR PRESSURE	VAPOR DENSITY			EVAPORAT	EVAPORATION RATE		
185 mmHg @ 20°C	(AIR = 1) Heavier than air				(BUTYL ACETATE =1) > 1.0		
SOLUBILITY IN WATER	% VOLATILE 34 – 52%			`	OTHER		
Slight				(IF ANY) None			
Slight VOC LBS./GAL 2.5 – 3.9 (IF ANY) None APPEARANCE							
AND ODOR Characteristic solvent odor	- clear liqu	uid					
SECTION IV-FIRE AND EXPLOSION HA							
	ZAKD DE		T	X 77X		TIL	
FLASH POINT - 4.0°F		1	FLAMMABLE LIMITS	LEL		EL	
(METHOD USED) TCC				1.0		12.8	
EXTINGUISHING							
MEDIA Carbon Dioxide, Dry Chen	nical, or Fo	oam					
SPECIAL FIRE							
	ned breath	ing apparatus wi	th a full face piece, operate	d in pressure demand	l or other positive	e pressure mode.	
UNUSUAL FIRE AND							
EXPLOSION HAZARDS This mater	ial is flam	mable and may b	e ignited by heat, sparks, f	ame or static electric	ity.		
HAZARDOUS PRODUCTS FORMED BY							
FIRE OR THERMAL DECOMPOSITION	Carbon	Dioxide and/or (Carbon Monoxide, Hydrog	en Chloride and orga	nic hydrocarbons	3.	
EXPLOSIVE LIMITS							
(% BY VOLUME IN AIR) 1.0 – 12.8							
SECTION V - OPTIONAL HAZARD RATI	NGS IDE	ENTIFICATION					
HAZARD RATING National Fire Protection Association (NFPA)							
4-EXTREME		`	ŕ				
3-HIGH			FIRE 3 REA	FIRE 3 REACTIVITY 0.			
2-MODERATE							
1-SLIGHT							
0-INSIGNIFICANT			HEALTH 2	HEALTH 2 SPECIAL HAZARDS None .			
**SEE SECTION IV							
						·	



CECTACALAN DE	OPPET TERMS A SAN	D COM L DAY AMAZ D L M L							
SECTION VI - REACTIVITY AND STABILITY DATA									
STABILITY	UNSTAI		CONDITIONS TO	O AVOID Temperatures over 350°F for over 10 minutes.					
INCOMPATIBILIT									
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide, Hydrogen Chloride, and other organic hydrocarbons.									
HAZARDOUS POLYMERIZATION	N	MAY OCCUR WILL NOT OCCUR X	CONDITIONS TO	O AVOID None					
SECTION VII - HEA									
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes									
HEALTH	ACUTE	X See Signs and Symptoms of Expo		TOW. 105 ETES. 105					
HAZARDS	CHRONIC	X See Signs and Symptoms of Expe	osuic ociow.						
CARCINOGENICIT		71							
SIGNS AND									
SYMPTOMS OF		Inhalation: Headache, nausea, and irritation of nose, throat and lungs.							
EXPOSURE		Skin: Irritation upon repeat or prolonged contact.							
EM OSCILE		Eyes: Slight irritation to eyes.							
MEDICAL CONDIT	TIONS CENER	RALLY AGGRAVATED BY EXPOSUR	F None known						
MEDICAL CONDIT	TONS GENER	CALLI AGGRAVATED DI EXI OSCI	TE None known						
EMERGENCY AND	`	Ingestion: Contact Physician or Poison	Control Immediatel	V					
FIRST AID	,	Ingestion: Contact Physician or Poison Control Immediately.							
PROCEDURES			Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary. Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician.						
PROCEDURES		Skin: Wash with soap and water.	of water. If iffication	ni persists, contact Physician.					
CECTION IVIII DD	EGA LITTIONIC I								
SECTION VIII - PR	ECAUTIONS I	FOR SAFE HANDLING AND USE							
STEPS TO BE TAK		Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.							
IN CASE MATERIA		Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material							
RELEASED OR SPI	ILLED	to dam or contain spills. If large spill, n	otify appropriate sta	ate and local agencies.					
WASTE DISPOSAL	METHODS D	Dispose of product in accordance with loca	l, county, state and	federal regulations.					
		-							
PRECAUTIONS TO	BE	Keep away from sparks, flame and heat sources. Store in cool ventilated area.							
TAKEN IN HANDLING		Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Avoid inhalation of vapors							
AND STORAGE		and personal contact with liquid produc	t. Use good persona	al hygiene practices.					
OTHER		Keep container closed when not in use. All containers should be disposed in an environmentally safe manner							
PRECAUTIONS		accordance with governmental regulation	ons.						
SECTION IX - CON	TROL MEASU	URES							
RESPIRATORY PR	OTECTION (S	SPECIFY TYPE) Depending on the Airbor	ne concentration,	PROTECTIVE GLOVES					
		OSH approved cartridge or supplied air equ		Rubber gloves					
VENTILATION	LOCAL EXH	HAUST Supplemental (if needed)		SPECIAL None					
		CAL (GENERAL) To maintain exposure	below PEL's.	OTHER None					
EYE PROTECTION		*		OTHER PROTECTIVE CLOTHING OR EQUIPMENT					
Chemical splash gogg	les or approved	eye protection.		Chemical Apron/Eye bath/Safety shower					
		Wash thoroughly after handling.		, , ,					
SECTION X - TRANSPORTATION INFORMATION (Optional)									
			DOT HAZ	ZARD CLASS 3					
DOT PROPER SHIPPING NAME Coating Solution DOT UN NUMBER UN 1139				DOT HAZARD CLASS 3 DOT PACKING GROUP II					
IATA PROPER SHIPPING NAME Coating Solution			IATA HAZARD CLASS 3						
IATA UN NUMBER UN 1139									
SECTION XI - 313 SUPPLIER NOTIFICATION									
	THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE								
	EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).								
Toluene, Methyl Ethyl Ketone, Xylene, and Ethylbenzene WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH									
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS. OR OTHER REPRODUCTIVE HARM.									

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	