


\*Estimate N/A-Not Applicable N/R-Not Restricted N/E-Not Established

## **MATERIAL SAFETY DATA SHEET**

NOTE: BLANK SPACES ARE NOT I	PERMITTED.	IF ANY ITEM IS	S NOT APPLICABLE, T	HE SPACE MUS	T BE MARKEI	TO INDICATE THAT.	
IDENTITY	PART NO.						
(As shown on Label or package)	(F-846, 847)	IF APPLICA	BLE				
SECTION I							
MANUFACTURER'S				EMERGENCY PHONE No.			
NAME Plasti Dip International Inc.				USA only: 1-800-424-9300 INT'L: 703-527-3887			
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE) 3920 Pheasant Ridge Drive				REVISION # 0003			
Blaine, MN 55449				MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156 DATE MSDS			
							WAS PREPA
SECTION II - HAZARDOUS INGREI	DIENTS INFO	RMATION. All I	Health Hazards which cor	nprise 1% or gre	ater of the comp	osition and all	
carcinogens if 0.1% of the composition	or greater.						
HAZARDOUS COMPONENTS CHE	MICAL and	% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS	
IDENTITY AND COMMON NA	ME (S)	(OPTIONAL)		PEL	TLV	RECOMMEND	
VM & P Naphtha		33.5 - 35.6	64742-89-8	300 ppm	300 ppm	None	
Heptane		14.5 – 15.1	426260-76-6	500 ppm	400 ppm	None	
Xylene		12.5 – 13.0	1330-20-7	100 ppm	100 ppm	None	
Methyl Ethyl Ketone		7.5 - 8.3	78-93-3	200 ppm	200 ppm	None	
Ethylbenzene		3.0 - 3.2	100-41-4	100 ppm	100 ppm	None	
SECTION III - PHYSICAL / CHEMIC	1			1			
BOILING 175 - 285°F	SPECIFIC	<b>GRAVITY</b> $(H_20 = 1)$	/	APPROXIMA		PER GALLON (LBS)	
POINT 79 - 141°C	0.79 - 0.83			6.67 - 6.87			
VAPOR PRESSURE	VAPOR DENSITY  (AID = 1) Hospitan than sin			EVAPORATION RATE (BUTYL ACETATE =1) > 1.0			
78 mmHg @ 20°C SOLUBILITY IN WATER	(AIR = 1) Heavier than air  % VOLATILE 71 - 75.2%			OTHER			
Insoluble	% VOLATILE 71 - 75.2% VOC LBS./GAL 4.8 - 5.0			(IF ANY) None			
APPEARANCE							
AND ODOR Various Colors, Honey	Like Substan	ce - Characteristic (	Odor				
SECTION IV-FIRE AND EXPLOSION							
<b>FLASH POINT</b> 20.0°F / -7°C	,		AMMABLE LIMITS	LEL		UEL	
(METHOD USED) TCC			0.9		11.5		
EXTINGUISHING		I					
MEDIA Carbon Dioxide, Dry	Chemical, or	Foam					
SPECIAL							
FIRE FIGHTING PROCEDURES Se	elf contained b	reathing apparatus v	with a full face piece, opera	ted in pressure der	mand or other pos	sitive pressure mode.	
UNUSUAL FIRE AND							
EXPLOSION HAZARDS This materi		and may be ignited	d by heat, sparks, flame or	static electricity.			
HAZARDOUS PRODUCTS FORMED BY							
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide.							
EXPLOSIVE LIMITS (% BY VOLUME IN AIR) 0.9 – 11.5							
	PATINGS ID	ENTIFICATION					
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION  HAZARD RATING  National Fire Protection Association (NFPA)							
HAZARD RATING 4-EXTREME			National Fire Frotection	on Association (IV	(FFA)		
3-HIGH			FIRE 3 REACTIV	FIRE 3 REACTIVITY 0.			
2-MODERATE		INC REACTIVITI					
1-SLIGHT							
0-INSIGNIFICANT			HEALTH 2 S	PECIAL HAZAF	RDS None	<u></u>	
**SEE SECTION IV							





-						
SECTION VI - REACTIVITY AN	ND STABILITY DATA					
STABILITY UNSTABLE STABLE X CONDITIONS TO AVOID None						
INCOMPATIBILITY (Materials t	to Avoid) Strong acids, bases, oxidizing	agents, selected amin	es with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide						
HAZARDOUS	MAY OCCUR	CONDITIONS TO AVOID				
POLYMERIZATION	WILL NOT OCCUR X		None			
SECTION VII - HEALTH HAZARD DATA						
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes						
HEALTH ACUTE	X See Signs and Symptoms of Exposure below.					
HAZARDS CHRONIC	X Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.					
CARCINOGENICITY: IARC 2B						
SIGNS AND						
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatig	nua Irragular Haartha	at Skin and Eva Irritation			
EXPOSURE			idneys, Lungs, Respiratory System, Skin.			
EATOSCRE	Target Organis. Crts, C v 5, 11 v 5, El v 61	i, Ridicys, Lungs, Re	spiratory bystem, okin.			
MEDICAL CONDITIONS GENE	RALLY AGGRAVATED BY EXPOSU	JRE Pre-existing Hea	rt. Liver. Kidney and Lung disorders.			
EMERGENCY AND	Ingestion: Contact Physician or Poison	Control Immediately				
FIRST AID	Inhalation: Remove to fresh air. Admi					
PROCEDURES	Eye Contact: Flush with large amounts	of water. If irritation	persists, contact Physician.			
	Skin: Wash with soap and water.					
SECTION VIII - PRECAUTIONS	FOR SAFE HANDLING AND USE					
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer		hood. Prevent run-off to sewers.			
IN CASE MATERIAL IS			te to maintain exposure below PEL's. Use sand or other material to dam			
RELEASED OR SPILLED	or contain spills. If large spill, notify appropriate state and local agencies.					
WACKE DISPOSAL MERHODS	B: 6 1 .: 1 ::11	1	10.1 1 1 1			
WASTE DISPOSAL METHODS	Dispose of product in accordance with le	ocal, county, state and	rederal regulations.			
PRECAUTIONS TO BE	Keen away from sparks flame and hea	t sources. Do not sto	re above 120°E and use adequate ventilation			
TAKEN IN HANDLING		at sources. Do not store above 120°F and use adequate ventilation.				
AND STORAGE	Avoid inhalation of vapors and contact with liquid product. Use good personal hygiene.					
THE OTOMICE						
OTHER	Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner					
PRECAUTIONS	in accordance with Governmental Regu	ılations.				
SECTION IX - CONTROL MEAS	SURES					
	(SPECIFY TYPE) Depending on the Airb		PROTECTIVE GLOVES			
	OSH approved cartridge or supplied air ed	quipment.	Impervious Gloves			
	IAUST Supplemental (if needed)		SPECIAL None			
MECHANICAL (GENERAL) To maintain exposure below PEL's OTHER None						
EYE PROTECTION	od ava mustaatian		OTHER PROTECTIVE CLOTHING OR EQUIPMENT			
Chemical splash goggles, or approved eye protection.  WORK HYGIENIC PRACTICES Wash thoroughly after handling.  Chemical Apron/Eye bath/Safety Shower						
SECTION X - TRANSPORTATION INFORMATION (Optional)   DOT PROPER SHIPPING NAME   Coating Solution   DOT HAZARD CLASS   3						
DOT UN NUMBER UN1139	E Coating Solution		DOT HAZARD CLASS 3 DOT PACKING GROUP II			
IATA PROPER SHIPPING NAME Coating Solution			IATA HAZARD CLASS 3			
IATA UN NUMBER UN 1139		IATA PACKING GROUP II				
SECTION XI - 313 SUPPLIER NOTIFICATION						
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE						
EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).						
Toluene and Methyl Ethyl Ketone		,	, , , , , , , , , , , , , , , , , , ,			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH						
DEFECTS OR OTHER REPRODUCTIVE HARM						

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	