

\*Estimated N/A-Not Applicable N/R-Not Restricted N/E-Not Established

## MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PER	MITTED. I	F ANY ITEM IS N	OT APPLICABLE,		UST BE MAR	KED TO INDICATE THAT.
IDENTITY		PART NO.				
(As shown on Label or package) F-886 Re-Rack				IF APPLICABLE		
SECTION I						
MANUFACTURER'S EMERGENCY PHONE No.						
NAME Plasti Dip Internation	al., Inc.			USA only: 1-800-424-9300 INT'L: 703-527-3887		
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE) 3920 Pheasant Ridge Drive				REVISION # 0001		
		MANUFACTURER'S PHONE				
Blaine, MN 55449				<b>No. FOR INFORMATION</b> 1-763-785-2156		
				DATE MSDS WAS PREPARED May 25, 2007		
SECTION II - HAZARDOUS INGREDIEN	NTS INFOR	MATION. All Hea	lth Hazards which c	omprise 1% or g	reater of the c	omposition and all
carcinogens if 0.1% of the composition or g	greater.					
HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)		% Wt. (OPTIONAL)	CAS NO.	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMEND
Xylene		53%	1330-20-7	100 ppm	100 ppm	None
Methyl Ethyl Ketone		10%	78-93-3	200 ppm	200 ppm	None
Ethylbenzene		13%	100-41-4	100 ppm	100 ppm	None
SECTION III - PHYSICAL / CHEMICAL				_		
BOILING	SPECIFIC	GRAVITY (H <sub>2</sub> O	= 1)	APPROXIMATE WEIGHT PER GALLON (LBS)		
<b>POINT</b> 175 - 279°F	0.85			7.05		
VAPOR PRESSURE	VAPOR DENSITY			EVAPORATION RATE (BUTYL ACETATE =1) >1.0		
78 mmHg @ 20°C SOLUBILITY IN WATER	(AIR = 1) Heavier than air % VOLATILE 76%			OTHER		
Insoluble	VOC LBS.			(IF ANY) None		
APPEARANCE						
AND ODOR Clear syrupy liquid, strong	odor					
SECTION IV-FIRE AND EXPLOSION HA	AZARD DA	ГА				
FLASH POINT 23°F		FLAMMABLE LIMITS		LEL		UEL
(METHOD USED) TCC				1.0		11.5
EXTINGUISHING						
MEDIA Carbon Dioxide, Dry Che	mical, or Foa	m				
SPECIAL FIRE			. 11 6		1 .1	
FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.						
UNUSUAL FIRE AND EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.						
HAZARDOUS PRODUCTS FORMED BY						
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide, Hydrogen Chloride and organic hydrocarbons.						
EXPLOSIVE LIMITS						
(% BY VOLUME IN AIR) 1.0 - 11.5						
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION						
HAZARD RATING			National Fire Pro	tection Associati	on (NFPA)	
4-EXTREME 3-HIGH						
2-MODERATE 1-SLIGHT			FIRE 3 REA	ACTIVITY	<u>.</u>	
0-INSIGNIFICANT						
**SEE SECTION IV			HEALTH 2	SPECIAL HA	ZARDS Non	е.
					<del></del>	

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY AND	STARII ITV DATA				
STABILITY UNSTAB		CONDITIONS	2500F C 10 ' 1		
	-		O AVOID Temperatures over 350°F for over 10 minutes.		
	Avoid) Oxidizing Materials, strong acids,				
			Hydrogen Chloride and some hydrocarbons.		
HAZARDOUS		CONDITIONS TO			
POLYMERIZATION	WILL NOT OCCUR X		None		
SECTION VII - HEALTH HAZARI	D DATA				
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes					
HEALTH ACUTE	X See Signs and Symptoms of Expos	ure below.			
HAZARDS CHRONIC	X				
CARCINOGENICITY: IARC 2B					
SIGNS AND					
SYMPTOMS OF	Inhalation: Headache, nausea, and irritati	on of nose, throat and lungs. Skin: Irritation upon repeat or			
EXPOSURE	prolonged contact. Eyes: Slightly irritation				
		•			
MEDICAL CONDITIONS GENER	ALLY AGGRAVATED BY EXPOSURE	None known			
EMERGENCY AND	Ingestion: Contact Physician or Poison C	ontrol Immediatel	y.		
FIRST AID	Inhalation: Remove to fresh air. Adminis	ster Oxygen or Art	er Oxygen or Artificial Respiration if Necessary.		
PROCEDURES Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician.					
	Skin: Wash with soap and water.		1 / 2		
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE					
SECTION VIII TRECTIONS I	OR SIN E INN (BER (G IN (B CSE				
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer to	hood Prevent ru	in off to sawars		
IN CASE MATERIAL IS					
RELEASED OR SPILLED		to maintain exposure below PEL's. Use sand or other material			
RELEASED OR SPILLED	to dam or contain spills. If large spill, app	propriate state and	local agencies.		
WASTE DISDOCAL METHODS D	:		C-111-4'		
WASTE DISPOSAL METHODS D	ispose of product in accordance with local,	county, state and	lederal regulations.		
PRECAUTIONS TO BE Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Keep away from sparks,					
PRECAUTIONS TO BE					
TAKEN IN HANDLING			rea. Avoid inhalation of vapors and personal contact with liquid		
AND STORAGE	product. Use good personal hygiene prac	tices.			
OTHER		te. Keep container closed when not in use. All containers should be			
PRECAUTIONS	disposed of in an environmentally safe ma	anner in accordance	ee with government regulations.		
SECTION IX - CONTROL MEASURES					
	PECIFY TYPE) Depending on the Airborne		PROTECTIVE GLOVES		
	SH approved cartridge or supplied air equip	ment.	Rubber gloves		
	AUST Supplemental (if needed)		SPECIAL None		
MECHANICA	L (GENERAL) To maintain exposure bel	ow PEL's.	OTHER None		
EYE PROTECTION			OTHER PROTECTIVE CLOTHING OR EQUIPMENT		
Chemical splash goggles or approved of			Chemical Apron/Eye bath/Safety shower		
WORK HYGIENIC PRACTICES Wash thoroughly after handling.					
SECTION X - TRANSPORTATION INFORMATION (Optional)					
DOT PROPER SHIPPING NAME	Coating Solution	DOT HAZARD CLASS 3			
DOT UN NUMBER UN 1139		DOT PACKING GROUP II			
IATA PROPER SHIPPING NAME Coating Solution		IATA HAZARD CLASS 3			
IATA UN NUMBER UN 1139		IATA PACKING GROUP II			
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE					
	EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).				
Xylene, Methyl Ethyl Ketone, Ethylber		,			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH					
DEFECTS, OR OTHER REPRODUCTIVE HARM.					

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	