



GET Plasti Dip Peel Coat

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 10/25/2018 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : GET Plasti Dip Peel Coat :
Product code GETF954154C3-UV
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Coating Solution.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Plasti Dip International, Inc.
3920 Pheasant Ridge Drive
Blaine, MN 55449
Phone: (763) 785-2156

Distributor

Plasti Dip UK Ltd
Harvesting Lane
East Meon GU32 1QR, UK
+44 (0) 1730 823 823

1.4. Emergency telephone number

Manufacturer Emergency number

CHEMTREC: 1-800-424-9300 (US);
+1 703-741-5970 (International)

Distributor Emergency Number

+44 (0) 1730 823 823

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Flammable liquids Category 2	H225
Skin corrosion/irritation Category 2	H315
Skin sensitization, Category 1	H317
Carcinogenicity Category 2	H351
Reproductive toxicity Category 2	H361
Specific target organ toxicity (single exposure) Category 3 - Narcosis	H336
Aspiration hazard Category 1	H304
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

GHS09

Signal word (CLP)

: Danger

Hazardous ingredients

: Distillates, petroleum, light distillate hydrotreating process, low-boiling; Naphtha, petroleum, hydrotreated light; Solvent naphtha, petroleum, light aliphatic; Octane; n-Heptane; Toluene; Ethylbenzene; Naphthalene; Methyl ethyl ketone; Cyclohexane; Hexane; Isopropyl alcohol; Carbon black; Methyl ethyl ketoxime

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H361 - Suspected of damaging fertility or the unborn child.
H411 - Toxic to aquatic life with long lasting effects.

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)

: P102 – Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective gloves, protective clothing.
P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor. Do NOT induce vomiting.
P370+P378 - In case of fire: Use foam, Carbon dioxide (CO₂), extinguishing powder to extinguish.
P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha, petroleum, hydrotreated light	(CAS-No.) 64742-49-0 (EC-No.) 265-151-9 (EC Index-No.) 649-328-00-1	30 – 60	Carc. 1B, H350* Muta. 1B, H340* Asp. Tox. 1, H304
Solvent naphtha, petroleum, light aliphatic	(CAS-No.) 64742-89-8 (EC-No.) 265-192-2 (EC Index-No.) 649-267-00-0	30 – 60	Muta. 1B, H340* Carc. 1B, H350* Asp. Tox. 1, H304
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS-No.) 68410-97-9 (EC-No.) 270-093-2 (EC Index-No.) 649-332-00-3	15 – 40	Muta. 1B, H340* Carc. 1B, H350* Asp. Tox. 1, H304
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	10 – 30	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
n-Heptane	(CAS-No.) 142-82-5 (EC-No.) 205-563-8 (EC Index-No.) 601-008-00-2	1 – 5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4	1 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Octane	(CAS-No.) 111-65-9 (EC-No.) 203-892-1 (EC Index-No.) 601-017-00-1	1 – 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2 (EC Index-No.) 601-017-00-1	5 – 10	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Methyl ethyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	0.1 – 1	Carc. 2, H351

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7 (EC-No.) 255-437-1	0.1 – 1	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	(CAS-No.) 82919-37-7 (EC-No.) 280-060-4	0.1 – 1	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	(C >= 5) STOT RE 2, H373

* Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of causing cancer (if route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). Causes damage to organs through prolonged or repeated exposure. May damage the unborn child. Suspected of damaging fertility.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Carbon dioxide. Dry chemical.
------------------------------	---------------------------------------

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Heating may cause an explosion.
Reactivity in case of fire	: None known.
Hazardous decomposition products in case of fire	: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon oxides and other organic compounds will be evolved when this material undergoes thermal degradation.

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

Precautionary measures fire	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: This material is flammable and may be ignited by heat, sparks, or static electricity.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment as described in section 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.
----------------------	---

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.
Methods for cleaning up	: Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Use only in well-ventilated areas. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep away from sources of ignition - No smoking.
-------------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep the container tightly closed. Store in a dry, cool and well-ventilated place. Keep away from ignition sources.
--------------------	---

7.3. Specific end use(s)

Coating Solution.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)

WELs not established

Naphtha, petroleum, hydrotreated light (64742-49-0)

WELs not established

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

WELs not established

Octane (111-65-9)

United Kingdom	WEL TWA (mg/m³)	1200 mg/m³
United Kingdom	WEL TWA (ppm)	210 ppm

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-Heptane (142-82-5)		
EU	IOELV TWA (mg/m³)	2085 mg/m³
EU	IOELV TWA (ppm)	500 ppm
United Kingdom	WEL TWA (ppm)	500 ppm

Toluene (108-88-3)		
EU	IOELV TWA (mg/m³)	192 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	384 mg/m³
EU	IOELV STEL (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m³)	191 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	384 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm

Benzene (71-43-2)		
EU	IOELV TWA (mg/m³)	3.25 mg/m³
EU	IOELV TWA (ppm)	1 ppm
United Kingdom	WEL TWA (ppm)	1 ppm

Ethylbenzene (100-41-4)		
EU	IOELV TWA (mg/m³)	442 mg/m³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m³)	884 mg/m³
EU	IOELV STEL (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m³)	441 mg/m³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m³)	552 mg/m³
United Kingdom	WEL STEL (ppm)	125 ppm

Naphthalene (91-20-3)		
United Kingdom	WEL TWA (mg/m³)	[53]* mg/m³
United Kingdom	WEL TWA (ppm)	[10]* ppm
United Kingdom	WEL STEL (mg/m³)	[80]* mg/m³
United Kingdom	WEL STEL (ppm)	[15]* ppm

Xylenes (o-, m-, p- isomers) (1330-20-7)		
EU	IOELV TWA (mg/m³)	221 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	442 mg/m³
EU	IOELV STEL (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m³)	220 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	441 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Cumene (98-82-8)		
EU	IOELV TWA (mg/m ³)	100 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	250 mg/m ³
EU	IOELV STEL (ppm)	50 ppm
United Kingdom	WEL TWA (mg/m ³)	125 mg/m ³
United Kingdom	WEL TWA (ppm)	25 ppm
United Kingdom	WEL STEL (mg/m ³)	375 mg/m ³
United Kingdom	WEL STEL (ppm)	75 ppm

Cyclohexane (110-82-7)		
EU	IOELV TWA (mg/m ³)	700 mg/m ³
EU	IOELV TWA (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m ³)	350 mg/m ³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m ³)	1050 mg/m ³
United Kingdom	WEL STEL (ppm)	300 ppm

Hexane (110-54-3)		
EU	IOELV TWA (mg/m ³)	72 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
United Kingdom	WEL TWA (mg/m ³)	72 mg/m ³
United Kingdom	WEL TWA (ppm)	20 ppm

Isopropyl alcohol (67-63-0)		
United Kingdom	WEL TWA (mg/m ³)	999 mg/m ³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m ³)	1250 mg/m ³
United Kingdom	WEL STEL (ppm)	500 ppm

Methyl ethyl ketone (78-93-3)		
EU	IOELV TWA (mg/m ³)	600 mg/m ³
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m ³)	900 mg/m ³
EU	IOELV STEL (ppm)	300 ppm
United Kingdom	WEL TWA (mg/m ³)	600 mg/m ³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m ³)	899 mg/m ³
United Kingdom	WEL TWA (ppm)	300 ppm

Limestone (1317-65-3)		
United Kingdom	WEL TWA (mg/m ³)	4 mg/m ³ respirable aerosol

Carbon black (1333-86-4)		
United Kingdom	WEL TWA (mg/m ³)	3.5 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	7 mg/m ³

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Barium sulfate (7727-43-7)		
EU	Remark (BLV – EU)	OELs not established
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ inhalable aerosol 4 mg/m ³ respirable aerosol

*The UK Advisory Committee on Toxic Substances has expressed concern that, for the OELs shown in parentheses, health may not be adequately protected because of doubts that the limit was not soundly-based. These OELs were included in the published UK 2002 list and its 2003 supplement, but are omitted from the published 2005 list.

8.2. Exposure controls

Appropriate engineering controls:

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment:

Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified and selected according to regional or national standards. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate PVC, or vinyl. Suitable gloves should be recommended by the glove supplier. [EN 374]

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles. [EN 166]

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure. [EN14605:2005 and EN 1304:2005]

Respiratory protection:

Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. [EN 137]

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Ignition sources. Heat. Sparks. Open flame. Static electricity.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.

Ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Naphthalene (91-20-3)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Cumene (98-82-8)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No information available.
Aquatic acute	: Not classified
Aquatic chronic	: Toxic to aquatic life with long lasting effects.

Hexane (110-54-3)

LC50 fish 1	2.1 - 2.98 mg/l 96 Hr LC50 Pimephales promelas [flow-through]
-------------	---

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

GET Plasti Dip Peel Coat

Persistence and degradability	No information available.
-------------------------------	---------------------------

12.3. Bioaccumulative potential

GET Plasti Dip Peel Coat

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

GET Plasti Dip Peel Coat

Ecology - soil	No information available.
----------------	---------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1139
UN-No. (IMDG)	: 1139
UN-No. (IATA)	: 1139
UN-No. (ADN)	: 1139
UN-No. (RID)	: 1139

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: COATING SOLUTION
Proper Shipping Name (IMDG)	: COATING SOLUTION
Proper Shipping Name (IATA)	: Coating solution
Proper Shipping Name (ADN)	: COATING SOLUTION
Proper Shipping Name (RID)	: COATING SOLUTION
Transport document description (ADR)	: UN 1139 COATING SOLUTION (Contains: Heptane, Methyl Ethyl Ketone, Petroleum Distillates), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 1139 COATING SOLUTION (Contains: Heptane, Methyl Ethyl Ketone, Petroleum Distillates), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 1139 Coating solution (Contains: Heptane, Methyl Ethyl Ketone, Petroleum Distillates), 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 1139 COATING SOLUTION (Contains: Heptane, Methyl Ethyl Ketone, Petroleum Distillates), 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 1139 COATING SOLUTION (Contains: Heptane, Methyl Ethyl Ketone, Petroleum Distillates), 3, II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Hazard labels (ADR)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3

Hazard labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3

Hazard labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Special provision (ADR) : 640C

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR) : TP1, TP8

Tank code (ADR) : L1.5BN

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Orange plates



Tunnel restriction code (ADR)

: D/E

EAC

: •3YE

Transport by sea (IMDG)

Limited quantities (IMDG)

: 5 L

Excepted quantities (IMDG)

: E2

Packing instructions (IMDG)

: P001

IBC packing instructions (IMDG)

: IBC02

Tank instructions (IMDG)

: T4

Tank special provisions (IMDG)

: TP1, TP8

EmS-No. (Fire)

: F-E

EmS-No. (Spillage)

: S-E

Stowage category (IMDG)

: B

Properties and observations (IMDG)

: Miscibility with water depends upon the composition.

Air transport (IATA)

PCA Excepted quantities (IATA)

: E2

PCA Limited quantities (IATA)

: Y341

PCA limited quantity max net quantity (IATA)

: 1L

PCA packing instructions (IATA)

: 353

PCA max net quantity (IATA)

: 5L

CAO packing instructions (IATA)

: 364

CAO max net quantity (IATA)

: 60L

Special provision (IATA)

: A3

ERG code (IATA)

: 3L

Inland waterway transport

Classification code (ADN)

: F1

Special provision (ADN)

: 640C

Limited quantities (ADN)

: 5 L

Excepted quantities (ADN)

: E2

Equipment required (ADN)

: PP, EX, A

Ventilation (ADN)

: VE01

Number of blue cones/lights (ADN)

: 1

Rail transport

Classification code (RID)

: F1

Special provision (RID)

: 640C

Excepted quantities (RID)

: E2

Packing instructions (RID)

: P001

Mixed packing provisions (RID)

: MP19

Portable tank and bulk container instructions (RID)

: T4

Portable tank and bulk container special provisions (RID)

: TP1, TP8

Tank codes for RID tanks (RID)

: L1.5BN

Transport category (RID)

: 2

Colis express (express parcels) (RID)

: CE7

Hazard identification number (RID)

: 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

Directive 2012/18/EU (SEVESO III)

GET Plasti Dip Peel Coat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory or are exempt

Germany

Reference to AwSV : Water hazard class (WGK) 3, strongly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Naphtha, petroleum, hydrotreated light, Benzene, Silica: Crystalline, quartz, Stoddard solvent are listed

SZW-lijst van mutagene stoffen : Naphtha, petroleum, hydrotreated light, Benzene, Stoddard solvent are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Hexane is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Toluene, Xylenes (o-, m-, p- isomers) are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes:

Revision 1.0: New SDS Created.

Other information : Author: TB

SDS Prepared for PlastiDip
International Company, Inc.
by:
Product Regulatory Services
Group
Pace Analytical Services, Inc.
1800 Elm Street
Minneapolis, MN 55414
United States
612-656-1122

Classification according to Regulation (EC) 1272/2008	
Flam. Liq. 2	Test Data
Aquatic Chronic 2	Calculation Method
Asp. Tox. 1	Calculation Method
Carc. 2	Calculation Method
Repr. 2	Calculation Method
Skin Irrit. 2	Calculation Method
Skin Sens. 1	Calculation Method
STOT SE 3 - Narcosis	Calculation Method
STOT RE 2	Calculation Method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product