

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : F-866 C3 BLACK
Product code : F866105C3
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : Coating

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Plasti Dip International, Inc.
3920 Pheasant Ridge Drive
Blaine, MN 55449
Phone - (763) 785-2156

Distributor

Global Express
7 Indian Path
Millstone, NJ 08535
(732) 977-0605

EU Importer of Record

Plasti Dip UK Ltd.
Unit 1, Harvesting Lane
GU32 1QR
United Kingdom

1.4. Emergency telephone number**Manufacturer Emergency number**

CHEMTREC: 1-800-424-9300 (US);
+1 703-741-5970 (International)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids Category 2	H225
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity Category 2	H361
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard Category 1	H304
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labeling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Precautionary statements (CLP)

H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

The mixture contains Methyl ethyl ketone (CAS#78-93-3), which is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605, at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates, petroleum, light distillate hydrotreating process, low-boiling	CAS-No.: 68410-97-9 EC-No.: 270-093-2 EC Index-No.: 649-332-00-3	15 – 40	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Naphtha, petroleum, hydrotreated light	CAS-No.: 64742-49-0 EC-No.: 265-151-9 EC Index-No.: 649-328-00-1	15 – 40	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
Solvent naphtha, petroleum, light aliphatic	CAS-No.: 64742-89-8 EC-No.: 265-192-2 EC Index-No.: 649-267-00-0	15 – 40	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Hexane	CAS-No.: 110-54-3 EC-No.: 203-777-6 EC Index-No.: 601-037-00-0	10 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	10 – 30	Flam. Liq. 2, H225 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methyl ethyl ketone	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3	3 – 7	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Octane	CAS-No.: 111-65-9 EC-No.: 203-892-1 EC Index-No.: 601-009-00-8	1 – 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
n-Heptane	CAS-No.: 142-82-5 EC-No.: 205-563-8 EC Index-No.: 601-008-00-2	1 – 5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Stoddard solvent	CAS-No.: 8052-41-3 EC-No.: 232-489-3 EC Index-No.: 649-345-00-4	0.1 – 1	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304 STOT RE 1, H372
Carbon black	CAS-No.: 1333-86-4 EC-No.: 215-609-9	0.1 – 1	Carc. 2, H351 STOT RE 1, H372

Full text of H- and EUH-statements: see section 16

SECTION 4: First Aid measures

4.1. Description of first aid measures

First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. Suspected of damaging the unborn child.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Dry chemical.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Explosion hazard : Heating may cause an explosion.
Reactivity in case of fire : None known.
Hazardous decomposition products in case of fire : Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon oxides and other organic compounds will be evolved when this material undergoes thermal degradation.

5.3. Advice for firefighters

Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : This material is flammable and may be ignited by heat, sparks, or static electricity.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.
Methods for cleaning up : Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Use only in well-ventilated areas. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep the container tightly closed. Store in a dry, cool and well-ventilated place. Keep away from ignition sources.

7.3. Specific end use(s)

Coating.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Naphtha, petroleum, hydrotreated light (64742-49-0)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	500 mg/m ³ (extraction)
NDSCh (OEL STEL)	1500 mg/m ³ (extraction (Benzin))
Octane (111-65-9)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1400 mg/m ³ (Octane all isomers)
MAK (OEL TWA) [ppm]	300 ppm (Octane all isomers)
MAK (OEL STEL)	5600 mg/m ³ (Octane all isomers)
MAK (OEL STEL) [ppm]	1200 ppm (Octane all isomers)
Belgium - Occupational Exposure Limits	
OEL TWA	1420 mg/m ³
OEL TWA	300 ppm
OEL STEL	1775 mg/m ³
OEL STEL	375 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	1450 mg/m ³
OEL STEL	1800 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	935 mg/m ³
OEL TWA [2]	200 ppm
OEL STEL	1870 mg/m ³
OEL STEL	400 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Octane (111-65-9)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	1400 mg/m ³ (Octane)
HTP (OEL TWA) [2]	300 ppm (Octane)
HTP (OEL STEL)	1800 mg/m ³
HTP (OEL STEL) [ppm]	380 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1450 mg/m ³
VME (OEL TWA) [ppm]	300 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	2400 mg/m ³
AGW (OEL TWA) [2]	500 ppm
AGW (OEL C)	4800 mg/m ³
AGW (OEL C) [ppm]	1000 ppm
Greece - Occupational Exposure Limits	
OEL TWA	2350 mg/m ³
OEL TWA	500 ppm
OEL STEL	2350 mg/m ³
OEL STEL	500 ppm
Hungary - Occupational Exposure Limits	
CK (OEL STEL)	4700 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	1450 mg/m ³
OEL TWA [2]	300 ppm
OEL STEL	4350 mg/m ³ (calculated)
OEL STEL	900 ppm (calculated)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1000 mg/m ³
NDSCh (OEL STEL)	1800 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	1500 mg/m ³
OEL TWA	322 ppm
OEL STEL	2000 mg/m ³
OEL STEL	429 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL C)	1400 mg/m ³ (Octanes)
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	1420 mg/m ³
VLA-ED (OEL TWA) [2]	300 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Octane (111-65-9)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1200 mg/m ³
WEL TWA (OEL TWA) [2]	210 ppm
Norway - Occupational Exposure Limits	
Grønseverdi (OEL TWA) [1]	725 mg/m ³
Grønseverdi (OEL TWA) [2]	150 ppm
Korttidsverdi (OEL STEL)	906.25 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	187.5 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	1400 mg/m ³
MAK (OEL TWA) [2]	300 ppm
KZGW (OEL STEL)	2800 mg/m ³
KZGW (OEL STEL) [ppm]	600 ppm
USA - ACGIH - Occupational Exposure Limits	
Local name	Octane, all isomers
ACGIH OEL TWA [ppm]	300 ppm
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2023
n-Heptane (142-82-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	2085 mg/m ³
IOEL TWA [ppm]	500 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	2000 mg/m ³
MAK (OEL TWA) [ppm]	500 ppm
MAK (OEL STEL)	8000 mg/m ³
MAK (OEL STEL) [ppm]	2000 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	1664 mg/m ³
OEL TWA	400 ppm
OEL STEL	2085 mg/m ³
OEL STEL	500 ppm
Denmark - Occupational Exposure Limits	
OEL TWA [1]	820 mg/m ³
OEL TWA [2]	200 ppm
OEL STEL	1640 mg/m ³
OEL STEL	400 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	1200 mg/m ³

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

n-Heptane (142-82-5)	
HTP (OEL TWA) [2]	300 ppm
HTP (OEL STEL)	2100 mg/m ³
HTP (OEL STEL) [ppm]	500 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1668 mg/m ³
VME (OEL TWA) [ppm]	400 ppm
VLE (OEL C/STEL)	2100 mg/m ³
VLE (OEL C/STEL) [ppm]	500 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	2100 mg/m ³
AGW (OEL TWA) [2]	500 ppm
AGW (OEL C)	2100 mg/m ³
AGW (OEL C) [ppm]	500 ppm
Ireland - Occupational Exposure Limits	
OEL TWA [1]	2085 mg/m ³
OEL TWA [2]	500 ppm
Italy - Occupational Exposure Limits	
OEL TWA	2085 mg/m ³
OEL TWA	500 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	350 mg/m ³
OEL TWA	85 ppm
OEL STEL	2085 mg/m ³
OEL STEL	500 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	1200 mg/m ³
TGG-15min (OEL STEL)	1600 mg/m ³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [2]	500 ppm
USA - ACGIH - Occupational Exposure Limits	
Local name	Heptane, isomers (n-Heptane)
ACGIH OEL TWA [ppm]	400 ppm
ACGIH OEL STEL [ppm]	500 ppm (listed under Heptane, all isomers)
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2024
Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³
IOEL TWA [ppm]	50 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
IOEL STEL	384 mg/m ³
IOEL STEL [ppm]	100 ppm
Notes	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
MAK (OEL TWA) [ppm]	50 ppm
MAK (OEL STEL)	380 mg/m ³
MAK (OEL STEL) [ppm]	100 ppm
Chemical category	skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m ³
OEL TWA	20 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	Skin, skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	192 mg/m ³
GVI (OEL TWA) [2]	50 ppm
KGVI (OEL STEL)	384 mg/m ³
KGVI (OEL STEL) [ppm]	100 ppm
Chemical category	skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Medium: final exhaled air - Sampling time: during exposure 2.5 g/g Kreatinin Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
Chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m ³
Chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g Kreatinin Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA [1]	94 mg/m ³
OEL TWA [2]	25 ppm
OEL STEL	188 mg/m ³
OEL STEL	50 ppm
Chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	81 mg/m ³
HTP (OEL TWA) [2]	25 ppm
HTP (OEL STEL)	380 mg/m ³
HTP (OEL STEL) [ppm]	100 ppm
Chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m ³ TWA [VME] (restrictive limit)
VME (OEL TWA) [ppm]	20 ppm TWA [VME] (restrictive limit)
VLE (OEL C/STEL)	384 mg/m ³ STEL [VLCT] (restrictive limit)

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
VLE (OEL C/STEL) [ppm]	100 ppm STEL [VLCT] (restrictive limit)
Chemical category	Risk of cutaneous absorption
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	190 mg/m ³
AGW (OEL TWA) [2]	50 ppm
AGW (OEL C)	760 mg/m ³
AGW (OEL C) [ppm]	200 ppm
Chemical category	skin notation
Germany - Biological limit values (TRGS 903)	
BLV	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: for long-term exposures: at the end of the shift after several shifts 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190
CK (OEL STEL)	380 mg/m ³
Chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA [1]	192 mg/m ³
OEL TWA [2]	50 ppm
OEL STEL	384 mg/m ³

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
OEL STEL	100 ppm
Chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
Chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
OEL TWA	14 ppm
OEL STEL	150 mg/m ³
OEL STEL	40 ppm
Chemical category	skin - potential for cutaneous exposure
Latvia - Biological limit values	
BEI (BLV)	1.6 g/g Kreatinin Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: end of shift
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m ³
IPRV (OEL TWA) [ppm]	50 ppm
TPRV (OEL STEL)	384 mg/m ³
TPRV (OEL STEL) [ppm]	100 ppm
Chemical category	Reproductive toxin, skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m ³
TGG-8u (OEL TWA) [ppm]	39 ppm
TGG-15min (OEL STEL)	384 mg/m ³
TGG-15min (OEL STEL) [ppm]	100 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³
NDSCh (OEL STEL)	200 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ (indicative limit value)
OEL TWA	50 ppm (indicative limit value)
OEL STEL	384 mg/m ³ (indicative limit value)
OEL STEL	100 ppm (indicative limit value)
Chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	192 mg/m ³
NPHV (OEL TWA) [2]	50 ppm
NPHV (OEL C)	384 mg/m ³
Chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 1600 mg/g Kreatinin Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	191 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
VLA-EC (OEL STEL)	384 mg/m ³
VLA-EC (OEL STEL) [ppm]	100 ppm
Chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KGV (OEL STEL)	384 mg/m ³
KGV (OEL STEL) [ppm]	100 ppm
Chemical category	skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	191 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	94 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
Chemical category	skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	190 mg/m ³
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	760 mg/m ³
KZGW (OEL STEL) [ppm]	200 ppm
Chemical category	skin notation, Category 2 reproductive toxin

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)

Switzerland - Biological limit values

BAT (BLV)	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g Kreatinin Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
-----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Turkey - Occupational Exposure Limits

OEL TWA	192 mg/m ³
OEL TWA	50 ppm
OEL STEL	384 mg/m ³
OEL STEL	100 ppm
Chemical category	skin notation

USA - ACGIH - Occupational Exposure Limits

Local name	Toluene
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2024

USA - ACGIH - Biological Exposure Indices

Local name	Toluene
BEI (BLV)	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g Kreatinin Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Regulatory reference	ACGIH 2024

Hexane (110-54-3)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	72 mg/m ³
IOEL TWA [ppm]	20 ppm

Austria - Occupational Exposure Limits

MAK (OEL TWA)	72
MAK (OEL TWA) [ppm]	20 ppm
MAK (OEL STEL)	288
MAK (OEL STEL) [ppm]	80 ppm

Belgium - Occupational Exposure Limits

OEL TWA	72 mg/m ³
---------	----------------------

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hexane (110-54-3)	
OEL TWA	20 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	72 mg/m³
OEL TWA	20 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	72 mg/m³
GVI (OEL TWA) [2]	20 ppm
Chemical category	skin notation
Croatia - Biological limit values	
BLV	150 µg/l Parameter: n-Hexane - Medium: blood - Sampling time: during exposure 40 ppm Parameter: n-Hexane - Medium: final exhaled air - Sampling time: during exposure 0.2 mg/g Kreatinin Parameter: 2-Hexanol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 5.3 mg/g Kreatinin Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	72 mg/m³
OEL TWA	20 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	70 mg/m³
Chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA [1]	90 mg/m³
OEL TWA [2]	25 ppm
OEL STEL	180 mg/m³
OEL STEL	50 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	72 mg/m³
OEL TWA	20 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	72 mg/m³
HTP (OEL TWA) [2]	20 ppm
Chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	72 mg/m³
VME (OEL TWA) [ppm]	20 ppm
Chemical category	Reproductive Toxin category 2

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hexane (110-54-3)	
France - Biological limit values	
BLV	Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	180 mg/m ³
AGW (OEL TWA) [2]	50 ppm
AGW (OEL C)	1440 mg/m ³
AGW (OEL C) [ppm]	400 ppm
Germany - Biological limit values (TRGS 903)	
BLV	5 mg/l Parameter: 2,5-Hexandione plus 4,5-Dihydroxy-2-hexanone (after hydrolysis) - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
Greece - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	72 mg/m ³
Chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA [1]	72 mg/m ³
OEL TWA [2]	20 ppm
OEL STEL	216 mg/m ³ (calculated)
OEL STEL	60 ppm (calculated)
Chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	72 mg/m ³
IPRV (OEL TWA) [ppm]	20 ppm
Chemical category	Reproductive toxin
Luxembourg - Occupational Exposure Limits	
OEL TWA	72 mg/m ³

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hexane (110-54-3)	
OEL TWA	20 ppm
Malta - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	72 mg/m ³
TGG-8u (OEL TWA) [ppm]	20 ppm
TGG-15min (OEL STEL)	144 mg/m ³
TGG-15min (OEL STEL) [ppm]	40 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	72 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	72 mg/m ³ (indicative limit value)
OEL TWA	20 ppm (indicative limit value)
Chemical category	skin - potential for cutaneous exposure
Romania - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
Romania - Biological limit values	
BLV	5 mg/g Kreatinin Parameter: 2,5-Hexandion - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	20 mg/m ³ 72 mg/m ³
NPHV (OEL C)	140 mg/m ³
Slovakia - Biological limit values	
BLV	5 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: end of exposure or work shift 5 mg/l Parameter: 4,5-Dihydroxy-2-hexanone - Medium: urine - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
OEL STEL	576 mg/m ³
OEL STEL	160 ppm
Chemical category	Category 2
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	72 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
Spain - Biological limit values	
BLV	0.2 mg/l Parameter: 2,5-Hexanedione - Medium: urine - Sampling time: end of workweek (without hydrolysis)

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hexane (110-54-3)	
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	72 mg/m ³
NGV (OEL TWA) [ppm]	20 ppm
KGV (OEL STEL)	180 mg/m ³
KGV (OEL STEL) [ppm]	50 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	72 mg/m ³
WEL TWA (OEL TWA) [2]	20 ppm
WEL STEL (OEL STEL)	216 mg/m ³ (calculated)
WEL STEL (OEL STEL) [ppm]	60 ppm (calculated)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	72 mg/m ³
Grenseverdi (OEL TWA) [2]	20 ppm
Korttidsverdi (OEL STEL)	108 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	30 ppm (value calculated)
Chemical category	Potential reproductive hazard
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	180 mg/m ³
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	1440 mg/m ³
KZGW (OEL STEL) [ppm]	400 ppm
Chemical category	skin notation, Category 2 reproductive toxin
Switzerland - Biological limit values	
BAT (BLV)	5 mg/l Parameter: 2,5-Hexanedione plus 4,5-Dihydroxy-2-hexanone - Medium: urine - Sampling time: end of shift
Turkey - Occupational Exposure Limits	
OEL TWA	72 mg/m ³
OEL TWA	20 ppm
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Hexane
ACGIH OEL TWA [ppm]	50 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
Regulatory reference	ACGIH 2023
USA - ACGIH - Biological Exposure Indices	
Local name	n-HEXANE
BEI (BLV)	0.5 mg/l Parameter: 2,5-Hexanedione without hydrolysis - Medium: urine - Sampling time: end of shift
Regulatory reference	ACGIH 2023

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Stoddard solvent (8052-41-3)	
Belgium - Occupational Exposure Limits	
OEL TWA	533 mg/m ³
OEL TWA	100 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	145 mg/m ³ (= <20% Aromatic compounds)
OEL TWA [2]	25 ppm (= <20% Aromatic compounds)
OEL STEL	290 mg/m ³ (= <20% Aromatic compounds)
OEL STEL	50 ppm (= <20% Aromatic compounds)
Estonia - Occupational Exposure Limits	
OEL TWA	300 mg/m ³
OEL TWA	50 ppm
OEL STEL	600 mg/m ³
OEL STEL	100 ppm
Greece - Occupational Exposure Limits	
OEL TWA	575 mg/m ³
OEL TWA	100 ppm
OEL STEL	720 mg/m ³
OEL STEL	125 ppm
Hungary - Occupational Exposure Limits	
Chemical category	Muta1B
Ireland - Occupational Exposure Limits	
OEL TWA [1]	573 mg/m ³
OEL TWA [2]	100 ppm
Chemical category	Carc1B
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³
IPRV (OEL TWA) [ppm]	50 ppm (approximate value)
TPRV (OEL STEL)	600 mg/m ³ (used as paint solvents and thinners, Ligroine containing 17-22% of Aromatic compounds (about 15-20% by volume) and the boiling range is approximately 150-200°C, the approximate size of the ppm calculated as White spirit containing 22% of Aromatic substances)
TPRV (OEL STEL) [ppm]	100 ppm (approximate value)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	300 mg/m ³ (varnish)
NDSCh (OEL STEL)	900 mg/m ³ (varnish (Benzin))
Portugal - Occupational Exposure Limits	
OEL TWA	100 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Stoddard solvent (8052-41-3)

Sweden - Occupational Exposure Limits

NGV (OEL TWA)	300 mg/m ³ (<2% aromatics) 175 mg/m ³ (2-25% aromatics)
NGV (OEL TWA) [ppm]	50 ppm (<2% aromatics) 30 ppm (2-25% aromatics)
KGV (OEL STEL)	600 mg/m ³ (<2% aromatics) 350 mg/m ³ (2-25% aromatics)
KGV (OEL STEL) [ppm]	100 ppm (<2% aromatics) 60 ppm (2-25% aromatics)
Chemical category	skin notation 2-25% aromatics, skin notation 2-25% aromatics

USA - ACGIH - Occupational Exposure Limits

Local name	Stoddard solvent
ACGIH OEL TWA [ppm]	100 ppm
Remark (ACGIH)	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2023

Carbon black (1333-86-4)

Belgium - Occupational Exposure Limits

OEL TWA	3 mg/m ³
---------	---------------------

Croatia - Occupational Exposure Limits

GVI (OEL TWA) [1]	3.5 mg/m ³
KGVI (OEL STEL)	7 mg/m ³

Czech Republic - Occupational Exposure Limits

PEL (OEL TWA)	2 mg/m ³ (dust)
---------------	----------------------------

Denmark - Occupational Exposure Limits

OEL TWA [1]	3.5 mg/m ³
OEL STEL	7 mg/m ³

Estonia - Occupational Exposure Limits

OEL TWA	3 mg/m ³
---------	---------------------

Finland - Occupational Exposure Limits

HTP (OEL TWA) [1]	3.5 mg/m ³
HTP (OEL STEL)	7 mg/m ³

France - Occupational Exposure Limits

VME (OEL TWA)	3.5 mg/m ³
---------------	-----------------------

Greece - Occupational Exposure Limits

OEL TWA	3.5 mg/m ³
OEL STEL	7 mg/m ³

Hungary - Occupational Exposure Limits

AK (OEL TWA)	3 mg/m ³ (inhalable concentration (flying and fibrous powders))
--------------	----------------------------------------------------------------------------

Ireland - Occupational Exposure Limits

OEL TWA [1]	3 mg/m ³ (inhalable fraction)
-------------	------------------------------------------

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Carbon black (1333-86-4)	
OEL STEL	15 mg/m ³ (calculated-inhalable fraction)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	4 mg/m ³ (inhalable fraction)
Portugal - Occupational Exposure Limits	
OEL TWA	3 mg/m ³ (inhalable fraction)
Chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	2 mg/m ³ (respirable fraction, 5% or less fibrogenic component) 10 mg/m ³ (respirable fraction, greater than 5% fibrogenic component) 10 mg/m ³ (total aerosol)
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	3.5 mg/m ³
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	3 mg/m ³ (inhalable fraction)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	3.5 mg/m ³
WEL STEL (OEL STEL)	7 mg/m ³
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	3.5 mg/m ³
Korttidsverdi (OEL STEL)	7 mg/m ³ (value calculated)
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH OEL TWA	3 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2024
Methyl ethyl ketone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	600 mg/m ³
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m ³
IOEL STEL [ppm]	300 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	295 mg/m ³
MAK (OEL TWA) [ppm]	100 ppm
MAK (OEL STEL)	590 mg/m ³
MAK (OEL STEL) [ppm]	200 ppm
Chemical category	skin notation

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Methyl ethyl ketone (78-93-3)	
Belgium - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	590 mg/m ³
OEL STEL	885 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	600 mg/m ³
GVI (OEL TWA) [2]	200 ppm
KGVI (OEL STEL)	900 mg/m ³
KGVI (OEL STEL) [ppm]	300 ppm
Croatia - Biological limit values	
BLV	2.6 mg/g Kreatinin Parameter: Ethyl methyl ketone - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	600 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	145 mg/m ³
OEL TWA [2]	50 ppm
OEL STEL	290 mg/m ³
OEL STEL	100 ppm
Chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	60 mg/m ³
HTP (OEL TWA) [2]	20 ppm
HTP (OEL STEL)	300 mg/m ³
HTP (OEL STEL) [ppm]	100 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Methyl ethyl ketone (78-93-3)	
Chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	600 mg/m ³
VME (OEL TWA) [ppm]	200 ppm
VLE (OEL C/STEL)	900 mg/m ³
VLE (OEL C/STEL) [ppm]	300 ppm
Chemical category	Risk of cutaneous absorption
France - Biological limit values	
BLV	Parameter: Methylethylketone - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	600 mg/m ³
AGW (OEL TWA) [2]	200 ppm
AGW (OEL C)	600 mg/m ³
AGW (OEL C) [ppm]	200 ppm
Chemical category	skin notation
Germany - Biological limit values (TRGS 903)	
BLV	2 mg/l Parameter: 2-Butanone - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	600 mg/m ³
CK (OEL STEL)	900 mg/m ³
Chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA [1]	600 mg/m ³
OEL TWA [2]	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Chemical category	Potential for cutaneous absorption

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Methyl ethyl ketone (78-93-3)

Italy - Occupational Exposure Limits

OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm

Latvia - Occupational Exposure Limits

OEL TWA	200 mg/m ³
OEL TWA	67 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm

Luxembourg - Occupational Exposure Limits

OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm

Malta - Occupational Exposure Limits

OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm

Netherlands - Occupational Exposure Limits

TGG-8u (OEL TWA)	590 mg/m ³
TGG-8u (OEL TWA) [ppm]	197 ppm
TGG-15min (OEL STEL)	900 mg/m ³
TGG-15min (OEL STEL) [ppm]	300 ppm
MAC chemical category	skin notation

Poland - Occupational Exposure Limits

NDS (OEL TWA)	590
NDSch (OEL STEL)	900

Portugal - Occupational Exposure Limits

OEL TWA	600 mg/m ³ (indicative limit value)
OEL TWA	200 ppm (indicative limit value)
OEL STEL	900 mg/m ³ (indicative limit value)
OEL STEL	300 ppm (indicative limit value)

Romania - Occupational Exposure Limits

OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Methyl ethyl ketone (78-93-3)	
Romania - Biological limit values	
BLV	2 mg/l Parameter: Methyleneethylketone - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	600 mg/m ³
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL C)	900 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA	200 ppm
OEL STEL	900 mg/m ³
OEL STEL	300 ppm
Chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	600 mg/m ³
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	900 mg/m ³
VLA-EC (OEL STEL) [ppm]	300 ppm
Spain - Biological limit values	
BLV	2 mg/l Parameter: Methyl ethyl ketone - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KGV (OEL STEL)	900 mg/m ³
KGV (OEL STEL) [ppm]	600 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	600 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	899 mg/m ³
WEL STEL (OEL STEL) [ppm]	300 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	220 mg/m ³
Grenseverdi (OEL TWA) [2]	75 ppm
Korttidsverdi (OEL STEL)	275 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	112.5 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	590 mg/m ³
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	590 mg/m ³

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Methyl ethyl ketone (78-93-3)	
KZGW (OEL STEL) [ppm]	200 ppm
Chemical category	skin notation
Switzerland - Biological limit values	
BAT (BLV)	2 mg/l Parameter: 2-Butanone - Medium: urine - Sampling time: end of shift, before subsequent shift or 16 hour 27.7 µmol/l Parameter: 2-Butanone - Medium: urine - Sampling time: end of shift, before subsequent shift or 16 hour
Turkey - Occupational Exposure Limits	
OEL TWA	600 mg/m³
OEL TWA	200 ppm
OEL STEL	900 mg/m³
OEL STEL	300 ppm
USA - ACGIH - Occupational Exposure Limits	
Local name	Methyl ethyl ketone (MEK)
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	300 ppm
Remark (ACGIH)	TLV® Basis: Embryo/fetal dam; URT irr; headache; dizziness. Notations: Skin; BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Methyl ethyl ketone
BEI (BLV)	2 mg/l Parameter: MEK - Medium: urine - Sampling time: end of shift (nonspecific)
Regulatory reference	ACGIH 2024

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles [EN 166]

8.2.2.2. Skin protection

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure. [EN 14605:2005 and EN 13034:2005]

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosion limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: 15 °C (59 °F) (VM&P Naphtha value)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle size	: Not applicable

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Ignition sources. Heat. Sparks. Open flame. Static electricity.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)

LD50 oral rat	5170 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 3000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat [ppm]	> 12408 ppm/4h

Naphtha, petroleum, hydrotreated light (64742-49-0)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg body weight Animal: rat
LD50 dermal rabbit	> 3160 mg/kg
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Naphtha, petroleum, hydrotreated light (64742-49-0)

LC50 Inhalation - Rat [ppm]	73680 ppm/4h
-----------------------------	--------------

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

LD50 oral rat	5000 mg/kg mouse; (Source: IUCLID)
---------------	------------------------------------

LD50 dermal rabbit	3000 mg/kg (Source: IUCLID)
--------------------	-----------------------------

Octane (111-65-9)

LD50 oral rat	> 5000 mg/kg Source: ECHA
---------------	---------------------------

LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
--------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------

LC50 Inhalation - Rat	118 g/m ³ 4 h
-----------------------	--------------------------

LC50 Inhalation - Rat (Vapours)	> 24.88 mg/l Source: ECHA
---------------------------------	---------------------------

n-Heptane (142-82-5)

LD50 oral rat	5000 mg/kg
---------------	------------

LD50 dermal rat	2800 – 3100 mg/kg body weight Animal: rat, Remarks on results: other:
-----------------	-----------------------------------------------------------------------

LD50 dermal rabbit	3000 mg/kg
--------------------	------------

LC50 Inhalation - Rat	103 g/m ³ 4h
-----------------------	-------------------------

Toluene (108-88-3)

LD50 oral rat	5000 mg/kg
---------------	------------

LD50 dermal rabbit	5000 mg/kg
--------------------	------------

LC50 Inhalation - Rat	384 mg/m ³
-----------------------	-----------------------

LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA
---------------------------------	------------------------

Hexane (110-54-3)

LD50 oral rat	25 g/kg (Source: NLM_CIP)
---------------	---------------------------

LD50 dermal rat	> 2000 mg/kg Source: ECHA
-----------------	---------------------------

LD50 dermal rabbit	3000 mg/kg
--------------------	------------

LC50 Inhalation - Rat [ppm]	48000 ppm/4h
-----------------------------	--------------

LC50 Inhalation - Rat (Vapours)	259.354 mg/l Source: ECHA
---------------------------------	---------------------------

Stoddard solvent (8052-41-3)

LD50 oral rat	5000 mg/kg Source: ChemIDplus
---------------	-------------------------------

LD50 dermal rabbit	> 3000 mg/kg (Source: ECHA_API)
--------------------	---------------------------------

LC50 Inhalation - Rat	> 5.5 mg/l/4h
-----------------------	---------------

Carbon black (1333-86-4)

LD50 oral rat	> 15400 mg/kg
---------------	---------------

LD50 dermal rat	> 2000 mg/kg (Source: ECHA)
-----------------	-----------------------------

LD50 dermal rabbit	> 3 g/kg
--------------------	----------

LC50 Inhalation - Rat	> 4.6 mg/m ³ (Exposure time: 4 h Source: ECHA_API)
-----------------------	---------------------------------------------------------------

Methyl ethyl ketone (78-93-3)

LD50 oral rat	2483 mg/kg (Source: JAPAN_GHS)
---------------	--------------------------------

LD50 oral	4000 mg/kg body weight
-----------	------------------------

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Methyl ethyl ketone (78-93-3)

LD50 dermal rabbit 5000 mg/kg (Source: JAPAN_GHS)

LC50 Inhalation - Rat [ppm] 11700 ppm/4h

LC50 Inhalation - Rat (Vapours) 32 mg/l Source: RTECS

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : May be fatal if swallowed and enters airways.

11.2. Information on other hazards

The mixture contains Methyl ethyl ketone (CAS#78-93-3), which is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605, at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

The mixture contains Methyl ethyl ketone (CAS#78-93-3), which is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605, at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	: UN 1139
UN-No. (IMDG)	: UN 1139
UN-No. (IATA)	: UN 1139
UN-No. (ADN)	: UN 1139
UN-No. (RID)	: UN 1139

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: COATING SOLUTION
Proper Shipping Name (IMDG)	: COATING SOLUTION
Proper Shipping Name (IATA)	: Coating solution
Proper Shipping Name (ADN)	: COATING SOLUTION
Proper Shipping Name (RID)	: COATING SOLUTION
Transport document description (ADR)	: UN 1139 COATING SOLUTION, 3, II, (D/E)
Transport document description (IMDG)	: UN 1139 COATING SOLUTION, 3, II
Transport document description (IATA)	: UN 1139 Coating solution, 3, II
Transport document description (ADN)	: UN 1139 COATING SOLUTION, 3, II
Transport document description (RID)	: UN 1139 COATING SOLUTION, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Hazard labels (ADR)	: 3

:



IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3

:



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

:



ADN

Transport hazard class(es) (ADN)	: 3
Hazard labels (ADN)	: 3

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



RID

Transport hazard class(es) (RID) : 3
Hazard labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provision (ADR) : 640D
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP8
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC : •3YE

Transport by sea (IMDG)

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Air transport (IATA)

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provision (ADN)	: 640D
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Special provision (RID)	: 640D
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory or are exempt.

Germany

Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Netherlands

- SZW-lijst van kankerverwekkende stoffen : Distillates, petroleum, light distillate hydrotreating process, low-boiling, Naphtha, petroleum, hydrotreated light, Solvent naphtha, petroleum, light aliphatic, Benzene, Cumene, Stoddard solvent are listed
- SZW-lijst van mutagene stoffen : Distillates, petroleum, light distillate hydrotreating process, low-boiling, Naphtha, petroleum, hydrotreated light, Solvent naphtha, petroleum, light aliphatic, Benzene, Stoddard solvent are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : Hexane is listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

Denmark

- Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
- Pregnant/breastfeeding women working with the product must not be in direct contact with the product
- The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

- Storage class (LK) : LK 3 - Flammable liquids

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-phrases

Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and acronyms	
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
ED	Endocrine disrupting properties
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LD50	Median lethal dose
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STOT	Specific target organ toxicity
TRGS	Technical Rules for Hazardous Substances
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Data sources	: Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Classification for the USA in accordance with 29 CFR 1910.1200 (2012). Classification for the EU in accordance with Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. ECHA (European Chemicals Agency).
Training advice	: Normal use of this product shall imply use in accordance with the instructions for use and corresponding product packaging.

Indication of changes:

Revision 3.0.

Other information	: Author: WJS.
-------------------	----------------

SDS prepared for Plasti Dip International, Inc. by:
Pace Analytical Services, Inc.
Product Regulatory Services Group
1800 Elm Street
Minneapolis, MN 55414
United States
612-656-1175

F-866 C3 BLACK

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

paceSDS@pacelabs.com

Classification according to Regulation (EC) No. 1272/2008	Classification procedure
Flammable liquids, Category 2	Test Data
Skin corrosion/irritation, Category 2	Specific concentration limit
Serious eye damage/eye irritation, Category 2	Specific concentration limit
Reproductive toxicity, Category 2	Specific concentration limit
Specific target organ toxicity – Single exposure, Category 3, Narcosis	Specific concentration limit
Specific target organ toxicity – Repeated exposure, Category 2	Specific concentration limit
Aspiration toxicity, Category 1	Specific concentration limit

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.