

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Plasti Dip® Spray Black
Product code : 10103S, 105C3S, 154C3S

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coating
Restrictions on use : Restricted in Arizona, California, Rhode Island, and Tennessee.

1.3. Supplier

Plasti Dip International, Inc.
3920 Pheasant Ridge Drive
Blaine, MN 55449
Phone - (763) 785-2156

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (US); +1 703-741-5970 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Skin Sens. 1 H317
Carc. 2 H351
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :
H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves, protective clothing, chemical goggles, & face protection.
P301+P310 - IF SWALLOWED: Immediately call poison center/doctor/...
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center or doctor if you feel unwell.
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Toluene	(CAS-No.) 108-88-3	15 - 40
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS-No.) 68410-97-9	15 - 40
Naphtha, petroleum, hydrotreated light	(CAS-No.) 64742-49-0	15 - 40
Solvent naphtha, petroleum, light aliphatic	(CAS-No.) 64742-89-8	15 - 40
Hexane	(CAS-No.) 110-54-3	7 - 13
Methyl ethyl ketone	(CAS-No.) 78-93-3	1 - 5
Octane	(CAS-No.) 111-65-9	1 - 5
n-Heptane	(CAS-No.) 142-82-5	1 - 5
Carbon black	(CAS-No.) 1333-86-4	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7	0.1 - 1
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidyl ester	(CAS-No.) 82919-37-7	0.1 - 1

*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child.

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: Product is not explosive.
Reactivity	: No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Material can splatter above 100 °C / 212 °F.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear Protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.
----------------------	---

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
-------------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep the container tightly closed. Avoid freezing.
--------------------	--

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)		
ACGIH	ACGIH OEL TWA [ppm]	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL (TWA) [2]	200 ppm
OSHA	OSHA PEL C [ppm]	300 ppm (500 ppm Peak [10 minutes])
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
OSHA	Remark (OSHA)	(2) See Table Z-2.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
IDLH	IDLH [ppm]	500 ppm
NIOSH	NIOSH REL (TWA)	375 mg/m³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
NIOSH	NIOSH REL (STEL)	560 mg/m³
NIOSH	NIOSH REL STEL [ppm]	150 ppm
Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Naphtha, petroleum, hydrotreated light (64742-49-0)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Solvent naphtha, petroleum, light aliphatic (64742-89-8)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Octane (111-65-9)		
ACGIH	ACGIH OEL TWA [ppm]	300 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL (TWA) [1]	2350 mg/m³
OSHA	OSHA PEL (TWA) [2]	500 ppm
OSHA	OSHA PEL (STEL) [1]	1800 mg/m³ Vacated
OSHA	OSHA PEL (STEL) [2]	375 ppm Vacated
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	1000 ppm (10% LEL)
NIOSH	NIOSH REL (TWA)	350 mg/m³
NIOSH	NIOSH REL TWA [ppm]	75 ppm
NIOSH	NIOSH REL (Ceiling)	1800 mg/m³
NIOSH	NIOSH REL C [ppm]	385 ppm
n-Heptane (142-82-5)		
ACGIH	ACGIH OEL TWA [ppm]	400 ppm

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Heptane (142-82-5)		
ACGIH	ACGIH OEL STEL [ppm]	500 ppm (listed under Heptane, all isomers)
ACGIH	Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL (TWA) [1]	2000 mg/m³
OSHA	OSHA PEL (TWA) [2]	500 ppm
OSHA	OSHA PEL (STEL) [1]	2000 mg/m³
OSHA	OSHA PEL (STEL) [2]	500 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Hexane (110-54-3)		
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL (TWA) [1]	1800 mg/m³
OSHA	OSHA PEL (TWA) [2]	500 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	1100 ppm (10% LEL)
NIOSH	NIOSH REL (TWA)	180 mg/m³
NIOSH	NIOSH REL TWA [ppm]	50 ppm
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Methyl ethyl ketone (78-93-3)		
ACGIH	ACGIH OEL TWA [ppm]	200 ppm
ACGIH	ACGIH OEL STEL [ppm]	300 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; CNS & PNS impair. Notations: BEI
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL (TWA) [1]	590 mg/m³
OSHA	OSHA PEL (TWA) [2]	200 ppm
OSHA	OSHA PEL (STEL) [1]	885 mg/m³
OSHA	OSHA PEL (STEL) [2]	300 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	3000 ppm
NIOSH	NIOSH REL (TWA)	590 mg/m³
NIOSH	NIOSH REL TWA [ppm]	200 ppm
NIOSH	NIOSH REL (STEL)	885 mg/m³
NIOSH	NIOSH REL STEL [ppm]	300 ppm
Carbon black (1333-86-4)		
ACGIH	ACGIH OEL TWA	3 mg/m³ (I - Inhalable particulate matter)

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon black (1333-86-4)		
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL (TWA) [1]	3.5 mg/m³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH	1750 mg/m³
NIOSH	NIOSH REL (TWA)	3.5 mg/m³ 0.1 mg/m³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≥ 4 °C / 39.2 °F (Toluene values)
Relative evaporation rate (butyl acetate=1)	: No data available

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Toluene (108-88-3)	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 Inhalation - Rat	384 mg/m ³
Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)	
LD50 oral rat	5170 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat [ppm]	> 12408 ppm/4h
Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 Inhalation - Rat [ppm]	73680 ppm/4h
Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
LD50 oral rat	5000 mg/kg mouse; (Source: IUCLID)
LD50 dermal rabbit	3000 mg/kg (Source: IUCLID)
Octane (111-65-9)	
LD50 oral rat	> 5000 mg/kg Source: ECHA

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Octane (111-65-9)	
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	118 g/m³ 4 h
n-Heptane (142-82-5)	
LD50 oral rat	5000 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg body weight Animal: rat, Remarks on results: other:
LD50 dermal rabbit	3000 mg/kg
LC50 Inhalation - Rat	103 g/m³ 4h
Hexane (110-54-3)	
LD50 oral rat	25 g/kg
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	3000 mg/kg
LC50 Inhalation - Rat [ppm]	48000 ppm/4h
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LD50 oral rat	2615 mg/kg
Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2483 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 Inhalation - Rat [ppm]	11700 ppm/4h
Carbon black (1333-86-4)	
LD50 oral rat	> 15400 mg/kg
LD50 dermal rabbit	> 3 g/kg
LC50 Inhalation - Rat	> 4.6 mg/m³ (Exposure time: 4 h)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: No data available
Symptoms/effects	: May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

12.2. Persistence and degradability

No additional information available

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1139 Coating solution (Contains: Toluene ; Octane ; n-Heptane), 3, II

UN-No.(DOT) : UN1139

Proper Shipping Name (DOT) : Coating solution
Contains: Toluene ; Octane ; n-Heptane

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 3 - Flammable liquid



DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 127

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description (TDG) : UN1139 COATING SOLUTION (Contains: Toluene ; Octane ; n-Heptane), 3, II

UN-No. (TDG) : UN1139

Proper Shipping Name (TDG) : COATING SOLUTION

TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids

Packing group (TDG) : II - Medium Danger

Explosive Limit and Limited Quantity Index : 5 L

Passenger Carrying Road Vehicle or Passenger : 5 L
Carrying Railway Vehicle Index

Transport by sea (IMDG)

Transport document description (IMDG) : UN 1139 COATING SOLUTION (Contains: Toluene ; Octane ; n-Heptane), 3, II

UN-No. (IMDG) : 1139

Proper Shipping Name (IMDG) : COATING SOLUTION

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 5 L

Air transport (IATA)

Transport document description (IATA)	: UN 1139 Coating solution (Contains: Toluene ; Octane ; n-Heptane), 3, II
UN-No. (IATA)	: 1139
Proper Shipping Name (IATA)	: Coating solution
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

PlastiDip® Spray Black	
All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Aspiration hazard Health hazard - Carcinogenicity Health hazard - Reproductive toxicity Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
Toluene (108-88-3)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
Hexane (110-54-3)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
Methyl ethyl ketone (78-93-3)	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Toluene (108-88-3)		X				7000 µg/day
Benzene (71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)
Ethylbenzene (100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Cumene (98-82-8)	X					

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Naphthalene (91-20-3)	X				5.8 µg/day	
Hexane (110-54-3)			X			28000 µg/day oral
Carbon black (1333-86-4)	X					
Silica: Crystalline, quartz (14808-60-7)	X					

Component	State or local regulations
Toluene (108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Benzene (71-43-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Ethylbenzene (100-41-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Octane (111-65-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
n-Heptane (142-82-5)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Naphthalene (91-20-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Hexane (110-54-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Methyl ethyl ketone (78-93-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Carbon black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Limestone (1317-65-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Silica: Crystalline, quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Stoddard solvent (8052-41-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Silica, amorphous (7631-86-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List
Barium sulfate (7727-43-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information


Revision Date : 03/19/2025
Other information : Author: WJS.

Plasti Dip® Spray Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



HMIS Hazard Rating

- Health : 3*
* - Chronic (long-term) health effects may result from repeated overexposure
- Flammability : 3
- Physical : 1

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.